

## Specification for Colorpoint (CP) 42oz

Construction: Yarn Content: Dye Method: Gauge: Width: Yarn Weight Tufted: Stitch Rate: Pile Height: Total Height:

Primary Backing: Secondary Backing: Pattern Repeat:

## Colorpoint Chromanyl Solution Dyed Nylon Solution Dyed 1/10th 12'0" | 15'0"(15ft is standard for RESERVE running line) 42 oz 12 SPI approx 0.315" standard backing approx 0.440" cushion backing approx 0.530" Woven Polypropylene Woven Polypropylene TBD

## Performance

Flame Resistance: Static Control: Flooring Radiant Panel: Smoke Density: Soil Resistance: Stain Resistance: Passes DOC FF-1-70 Less than 3.5 KV Class 1 (ASTM 648) Less than .450 (ASTM E622) Commercial Anti-Soil Protection Commercial Stain Protection

## Warranties

Wear: Static: Colorfastness: 10 Year Limited Lifetime Limited Lifetime Limited

Tufted pile weight is based on material post production; pattern and shear amounts may alter final tufted pile weight.

All specifications subject to normal manufacturing tolerances.

Encore Hospitality flooring products are to be installed in full accordance with Encore's installation instructions and standard trade practices. A program of regular cleaning and maintenance is vital for retaining a high appearance level. Installation plus Care & Maintenance manuals can be downloaded at www.encorecarpet.net