

## Specification for Infinity (IN) 36oz Tip Shear

Construction:	Infinity Tip Shear
Yarn Content:	Chromanyl Solution Dyed Nylon
Dye Method:	Solution Dyed
Gauge:	1/10th
Width:	12' (up to 15' available)
Yarn Weight Tufted:	36 oz
Stitch Rate:	13.5 SPI
Primary Backing:	Woven Polypropylene
Secondary Backing:	Contract Unitary
Pile Height:	approx 0.250"
Total Thickness:	standard backing approx 0.375" cushion backing approx 0.465"
Pattern Repeat:	TBD

---

### Performance

Flame Resistance:	Passes DOC FF-1-70
Static Control:	Less than 3.5 KV
Flooring Radiant Panel:	Class 1 (ASTM 648)
Smoke Density:	Less than .450 (ASTM E622)
Soil Resistance:	Commercial Anti-Soil Protection
Stain Resistance:	Commercial Stain Protection

---

### Warranties

Wear:	10 Year Limited
-------	-----------------

Tufted pile weight is based on material post production; pattern and shear amounts may alter final tufted pile weight.

All specifications subject to normal manufacturing tolerances.

Encore Hospitality flooring products are to be installed in full accordance with Encore's installation instructions and standard trade practices. A program of regular cleaning and maintenance is vital for retaining a high appearance level. Installation plus Care & Maintenance manuals can be downloaded at [www.encorecarpet.net](http://www.encorecarpet.net)